

Integra®

DTR-6.9

THX SELECT2 PLUS, 2-ZONE
7.1 CHANNEL SURROUND RECEIVER



FEATURES

AMPLIFICATION:

- 7 x 125 Watts/Channel at 6Ω
- 7 x 100 Watts/Channel at 8Ω
- Certified 4Ω Performance
- Discrete Output Stages for All Channels
- Wide Range Amplifier Technology — WRAT (5 Hz - 100 kHz)
- Fine Linear Optimum Gain Volume Circuitry
- High Current Power Supply (H.C.P.S.)
- Bi-amp Capability for Front L/R Channels

PROCESSING:

- THX™ Select2 Plus Certified
- THX™ Loudness Plus for Enhanced Surround Detail
- HDMI™ (v.1.3a with 1080p Support, Deep Color, LipSync)
- Faroudja DCDi Cinema HDMI Upscaling from Analog Sources (to 1080p)
- Dolby® TrueHD, Dolby® Digital Plus, DTS-HD® Master Audio, DTS-HD® High-Resolution Audio Decoding
- Audyssey MultEQ™ Advanced Room Correction
- Audyssey Dynamic EQ™ For Loudness Correction
- Two Advanced TI (Aureus™) 32-Bit Processing DSP Chips
- Cirrus Logic 192 kHz/24-bit DACs for All Channels
- A-Form Listening Mode Memory and IntelliVolume Input Level Calibration System
- Music Optimizer to Enhance Compressed Music Files
- Independent Crossover Adjustment for F/C/S/SB
- 15-band Graphic Equalizer
- A/V Synchronization Function (Up to 250 ms in 2 ms Steps)

CONNECTIONS:

- 1080p Deep Color™ (36 bit) Capable HDMI (4in/1out) w/Upconversion/Transcoding from Analog Sources
- HD Component Video Switching (3in/2out, 50 MHz)
- SIRIUS Ready through SiriusConnect Home Tuner Kit
- XM Ready through XM Mini Tuner and Home Dock
- Assignable Digital Inputs (4 HDMI, 2 Optical, 3 Coaxial)
- HDMI/Component Video Assignable to Tape/CD/Phono
- Front Panel A/V Inputs (including optical)
- Color-Coded 7.1-Multichannel Inputs and Pre Outs

CUSTOM INTEGRATION FEATURES:


- Bi-directional RS-232 & Ethernet Port for 3rd Party Control Systems
- Powered Zone 2 and Zone 2 Pre-Out with Bass/Treble/Balance Control and HD Component Video
- Main Zone & Zone 2 Max & Power On Volume Settings
- IntelliZone for Second Room Playback and Control
- Dealer Settings Memory Store & Recall with Lock/Unlock
- Permanently Stored Memory Settings
- Dual IR Inputs With Common Output
- 3 Unique Assignable IR Code Sets
- 3 Programmable 12V triggers (With Adjustable Delay)
- RIHD (Remote Interactive over HDMI)
- Optional Rack Mount Kit Available- IRK-155-3A

Designed to Integrate. Built to Stimulate.

Integra®

DTR-6.9

THX SELECT2 PLUS, 2-ZONE 7.1 CHANNEL SURROUND RECEIVER



SPECIFICATIONS

AMPLIFIER

Continuous average power output (FTC)
All channels: 100 W per channel min. RMS at 8Ω, 2 channels driven from 20 Hz to 20 kHz with no more than 0.08% total harmonic distortion.
115 W min. RMS at 6Ω, 2 channels driven from 1 kHz with no more than 0.1% total harmonic distortion.

Dynamic power output (stereo): 2 × 240 W at 3Ω
2 × 210 W at 4Ω
2 × 120 W at 8Ω

Frequency response: 5 Hz to 100 kHz: +1/-3 dB
Signal-to-noise ratio: 106 dB (LINE, IHF-A)
Total harmonic distortion: 0.08% at rated power
IM distortion: 0.08% at rated power
Damping factor: 60 at 8Ω
Speaker impedance: 4Ω to 16Ω

INPUT SENSITIVITY AND IMPEDANCE

Line: 200 mV, 47 kΩ

OUTPUT LEVEL AND IMPEDANCE

Rec out: 200 mV, 470Ω
Pre out: 1 V, 470Ω
Zone 2 line output: 100 mV, 470Ω

TONE CONTROL

Bass: ±10 dB at 50 Hz
Treble: ±10 dB at 20 kHz

FM

Tuning range: 87.5-107.9 MHz (100-kHz steps)
Usable sensitivity, stereo: 22.2 dBf, 2.0 μV (75Ω IHF)

AM

Tuning range: 530-1,710 kHz (10-kHz steps)
Usable sensitivity: 300 μV/m



DIGITAL TUNER

*XM, SIRIUS

GENERAL

Power supply: AC 120 V, 60 Hz
Power consumption: 5.9 A
Dimensions (W x H x D): 17-1/8 x 6-3/4 x 15-3/8
435 x 172 x 391
Weight: 27.4 lbs. (12.4 kg)
Optional mounting kit: IRK-155-3A
U dimension: 4U

*SIRIUS requires separate purchase of subscription and SiriusConnect Home Tuner Kit.
XM requires separate purchase of subscription and XM Mini-tuner and home dock



"XM" is a registered trademark of XM Satellite Radio Holdings, Inc.
"SIRIUS" is a registered trademark of SIRIUS Satellite Radio Inc.
"THX" is a trademark of THX Ltd.
All others are trademarks or registered trademarks of their respective holders.
Due to a policy of continuous product improvement, Integra reserves the right to change specifications and appearance without notice.
06/2008 Printed in the USA

Designed to Integrate. Built to Stimulate.

www.integrahometheater.com